

ADA 0 58389

DOC FILE COP





Efficient Model for HF Lasers with Rotational Nonequilibrium

J. J. T. HOUGH
Aerophysics Laboratory
The Ivan A. Getting Laboratories
The Aerospace Corporation
El Segundo, Calif. 90245

15 August 1978

Interim Report

DDC SEP 7 1978

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

Prepared for NAVAL SEA SYSTEMS COMMAND Washington, D.C. 90362

SPACE AND MISSILE SYSTEMS ORGANIZATION AIR FORCE SYSTEMS COMMAND Los Angeles Air Force Station P.O. Box 92960, Worldway Postal Center Los Angeles, Calif. 90009

78 08 31 025

This interim report was submitted by The Aerospace Corporation, El Segundo, CA 90245, under Contract No. F04701-77-C-0078 with the Space and Missile Systems Organization, Deputy for Advanced Space Programs, P.O. Box 92960, Worldway Postal Center, Los Angeles, CA 90009. It was reviewed and approved for The Aerospace Corporation by W. R. Warren, Jr., Director, Aerophysics Laboratory. Lieutenant Arturo G. Fernandez, SAMSO/YCPT, was the project officer for Advanced Space Programs.

This report has been reviewed by the Information Office (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication. Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

Arturo G. Fernandez, Lt, USAF

Project Officer

Chief, Technology Plans Division

FOR THE COMMANDER

Floyd R. Stuart, Colonel, USAF

Deputy for Advanced Space Programs

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

| | RESORT DOCUMENTATION PAGE | READ INSTRUCTIONS BEFORE COMPLETING FORM | |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|--|
| | | . 3. RECIPIENT'S CATALOG NUMBER | |
| - | SAMSO TR - 78-79 | 5. TYPE TE REPORT & PERIOD COVERED | |
| 1 | | (9) | |
| | EFFICIENT MODEL FOR HE LASERS WITH ROTATIONAL NONEQUILIBRIUM | Interim Peplis | |
| 7 | | TR-0078(3725)-2 | |
| 1 | AUTHOR(s) | C. LCONTRACT ON GRANT NUMBER(s) | |
| (| Joseph J. T. Hough | 5 F \$47\$1-77-C-\$\$78 | |
| 1 | 9. PERFORMING ORGANIZATION NAME AND ADDRESS | 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS | |
| | The Aerospace Corporation El Segundo, Calif. 90245 | | |
| 1 | 11. CONTROLLING OFFICE NAME AND ADDRESS | 15 August 1978 | |
| 1 | Naval Sea Systems Command | 13. NUMBER OF PAGES | |
| 1 | Washington, D. C. 90362 14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office) | 18 15. SECURITY CLASS. (of this report) | |
| 1 | Space and Missile Systems Organization | | |
| 1 | Air Force Systems Command | Unclassified 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE | |
| 1 | Los Angeles, Calif. 90009 | SCHEDULE | |
| | 16. DISTRIBUTION STATEMENT (of this Report) | | |
| 1 | (12) 18 P' | | |
| 1 | Approved for public release; distribution unlimi | ted | |
| 1 | | | |
| 1 | 17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different from | om Report) | |
| 1 | | | |
| 1 | | | |
| T | 18. SUPPLEMENTARY NOTES | | |
| 1 | | | |
| 1 | | | |
| 1 | 19. KEY WORDS (Continue on reverse side if necessary and identify by block number, |) | |
| 1 | HF Lasers | | |
| 1 | | | |
| 1 | | | |
| 1 | 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) | | |
| ١ | A method for modeling rotational nonequilibrium in HF(DF) laser systems | | |
| ١ | that significantly reduces the computation time required for such calculations is described. With this formulation, an approximation can be obtained of the | | |
| 1 | nonequilibirum optical gains of the individual v, | J transitions without com- | |
| 1 | puting the individual populations for each v, J st duces the number of integration variables. The | predictions of a pulsed | |
| 1 | Ho-F' laser model utilizing this approach are v | very similar to the predictions | |

DD FORM 1473

UNCLASSIFIED

UNCLASSIFIED


UNCLASSIFICATION OF THIS PAGE (When Date Entered)

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered) 19. KEY WORDS (Continued) 20. ABSTRACT (Continued) of a more complex model. The computational economy gained makes feasible parametric studies to improve understanding of the importance of rotational relaxation in laser calculations.

UNCLASSIFIED

CONTENTS

| EFFECIENT MODEL FOR HF LASERS WITH ROTATIONAL NONEQUILIBRIUM | 1 |
|--------------------------------------------------------------------------|----|
| Fig. 1. Comparison of Pulse Outputs Predicted by Present Model and ROLAX | 10 |
| Fig. 2. Comparison of Time-Resolved Spectra of Present Model and ROLAX | 12 |
| REFERENCES | 15 |



EFFICIENT MODEL FOR HF LASERS WITH ROTATIONAL NONEOUILIBRIUM

Rotational relaxation and rotational hole-burning play an important role in determining the degree of saturation and the rate at which energy can be extracted from a chemical-laser medium. Model predictions of laser output energy, spectral content, and performance under line-selected operation are more realistic when rotational-relaxation mechanisms are included. Mode structure and mode competition within an optical cavity are directly related to the distribution of gain and losses within the cavity. Laser-output beam-quality predictions should be made with a model that can accurately predict the gain distribution within the active medium. Satisfactory prediction of gain distribution requires that the effects of rotational non-equilibrium be considered.

Rotational relaxation has been modeled either by means of detailed rotational kinetics 1-6 or by use of a rotational relaxation time constant. 6,7 The detailed kinetics model is more realistic, and appears to have the potential of being able to predict time histories of the laser transitions in all the comprehensive detail that is seen in experiments. In contrast, a time constant model seems to display the dominant features of this time-resolved spectra while missing some fine details. Preliminary comparisons of laser output energy and spectral energy distributions, however, have not shown substantial differences in the two modeling approaches. 6 More exhaustive comparisons between the models and with experimental spectra need to be

carried out in order to identify regimes where the additional realism afforded by the detailed kinetics model will be required.

A difficulty with HF laser models treating finite rate rotational relaxation is their need for large amounts of computation time. The method described here increases the efficiency of models in which the time-constant approach is used. This new scheme drastically reduces the computational time, with little loss of accuracy. In a comparison with a comprehensive earlier model (ROLAX)⁶ for chain-reaction HF lasers, the number of integration variables can be reduced from 179 to 65, and computation times are typically shorter by a factor of 10 or more. For the two models, predictions of pulse energy, pulse length, and spectral energy distribution typically agree within 5%.

Formulation of the new model through our Eq. (4) is identical to that given in Ref. 7. This material is recapitulated very briefly. The major assumptions are: (1) Kinetic processes are represented by 164 reactions, based on the survey by Cohen. (2) The reacting mixture is homogeneous and contained in a Fabry-Perot laser cavity. (3) Lasing is assumed to be always in the P-branch and restricted to the first fifteen transitions in each of the lowest six vibrational bands. (4) All transitions are assumed to have low initial intensities, which grow if the gains rise above threshold.

HF vibration-rotation state populations N(v, J) are computed from the kinetic reactions, with the effects of lasing, absorption, and spontaneous emission taken into account.

The gain coefficient is

$$\alpha(\mathbf{v},\mathbf{J}) = \frac{hN_{\mathbf{A}}}{4\pi} \omega_{\mathbf{C}}(\mathbf{v},\mathbf{J}) \varphi_{\mathbf{C}} B(\mathbf{v},\mathbf{J}) \left[\frac{g_{\ell}}{g_{\mathbf{u}}} N(\mathbf{v}+1,\mathbf{J}-1) - N(\mathbf{v},\mathbf{J}) \right]$$
(1)

where v and J are quantum numbers of the lower level of the transition, $\mathbf{w}_{\mathbf{c}}(\mathbf{v},\mathbf{J})$ is the wavenumber of the transition, $\mathbf{B}(\mathbf{v},\mathbf{J})$ is an Einstein coefficient, $\mathbf{g}_{\mathbf{u}}$ and \mathbf{g}_{ℓ} are upper and lower state degeneracies, respectively, and $\mathbf{N}(\mathbf{v},\mathbf{J})$ are state populations. Both Doppler and pressure broadening are considered through use of a Voigt profile $\varphi_{\mathbf{c}}$, which is evaluated at line center.

The rate of photon extraction per unit volume is

$$X_{\rm rad}(v,J) = \alpha(v,J) f(v,J)$$
 (2)

where f(v, J) is photon flux. The rate equation for f is

$$\frac{\mathrm{df}(\mathbf{v},\mathbf{J})}{\mathrm{dt}} = c\left(\frac{\mathbf{L}}{\ell}\right) \left[\alpha(\mathbf{v},\mathbf{J}) - \alpha_{\mathrm{th}}\right] f(\mathbf{v},\mathbf{J}) \tag{3}$$

where c is the speed of light and

$$\alpha_{th} = -\frac{1}{2L} \ln (R_{O}R_{L}) \tag{4}$$

where L is the length of the active medium, ! is the mirror spacing, and RO and RI are mirror reflectivities.

For brevity and clarity, the new rotational relaxation model is explained in terms of a single vibrational band laser. A discussion of the formulation for a multiband laser with cascading will be given elsewhere because of its length. Numerical results given here, however, are for the full multiband model.

Let $N_{u}(J)$ and $N_{\ell}(J')$ denote the upper and lower state populations, respectively, of a laser transition with photon flux f. The rate equations for the populations may be written

$$\frac{dN_{u}(J)}{dt} = -\alpha f + \frac{N_{u}^{e}(J) - N_{u}(J)}{\tau_{u}(J)}$$
 (5a)

and

$$\frac{\mathrm{d}N_{\ell}(J')}{\mathrm{d}t} = \alpha f + \frac{N_{\ell}^{\mathrm{e}}(J') - N_{\ell}(J')}{\tau_{\ell}(J')}$$
 (5b)

where $N_i^e(J)$ is the instantaneous rotationally equilibrated concentration of $N_i(J)$ and $\tau_i(J)$ is the time constant for rotational relaxation of level $N_i(J)$.

The rotational relaxation mechanism represented by Eq. (5) is identical to the formulation used in Ref. 7, except that preferential (i.e., Jeselective) pumping and deactivation are ignored. Here, individual rotational states are fed (or depleted) only through rotational relaxation or lasing. Pumping and vibrational-state deactivation are manifested indirectly through their effect on N^e terms.

The relaxation time τ is assumed to depend on the energy separation of adjacent rotational states. The form 7

$$\tau_{\rm J} \sim A_{\rm J} \exp\left(\frac{B\Delta E_{\rm J}}{kT}\right)$$
 (6)

is used, where A_J^{-1} is proportional to the frequency for binary collisions with all partners, B is a constant, and ΔE_J is the energy separation of adjacent rotational states.

For P-branch transitions a useful approximation is

$$\tau_{11} \cong \tau_{\ell} \equiv \tau \tag{7}$$

For this single-band system, Eq. (1) may be written

$$\alpha(J) = \phi \left[\frac{g_{\ell}}{g_{u}} N_{u}(J) - N_{\ell}(J') \right]$$
 (8)

where ϕ_J represents all quantities outside the brackets in Eq. (1). A rotationally equilibrated gain α^e is defined as

$$\alpha^{\mathbf{e}}(\mathbf{J}) = \phi \left[\frac{\mathbf{g}_{\ell}}{\mathbf{g}_{\mathbf{u}}} \ \mathbf{N}_{\mathbf{u}}^{\mathbf{e}}(\mathbf{J}) - \mathbf{N}_{\ell}^{\mathbf{e}}(\mathbf{J}') \right]$$
 (9)

Differentiating Eq. (8) with respect to time, and substituting Eqs. (5) and (7) through (9), one obtains

$$\frac{d\alpha}{dt} = -\phi \left(\frac{g_{\ell}}{g_{u}} + 1 \right) \alpha f + \frac{\alpha^{e} - \alpha}{\tau}$$
 (10)

At saturation, $\alpha \cong \alpha_{th} = constant$. Therefore, $d\alpha/dt = 0$ and Eq. (10) can be solved for α to obtain

$$\alpha = \frac{\alpha^{e}}{1 + f/f_{s}} \tag{11}$$

where the "saturation flux" f_s is defined by

$$f_{s} = \frac{1}{\phi \left[(g_{\ell} / g_{u}) + 1 \right] \tau}$$
 (12)

Although Eq. (11) was derived with the use of the saturation assumption, it is clearly valid for the case $f \ll f_s$ since it reduces to $\alpha \cong \alpha^e$. The calculations in Ref. 7 from a rotational equilibrium model ($\alpha = \alpha^e$) indicate that the saturation process is rapid enough such that, prior to saturation, the condition $f \ll f_s$ generally holds. Thus, Eq. (11) may be taken to apply at all times with very little error. This result makes it possible to predict the nonequilibrium gains of the individual vibrational-rotational transitions directly from the vibrational populations and the photon fluxes of the corresponding transitions. The need to compute instantaneous rotational state populations is avoided, thus eliminating them as required integration variables.

A rotational bottle-necking effect is clearly demonstrated by Eq. (11). The observed laser intensity depends on the magnitude of the saturation intensity f_s , i.e., for small f_s , f must remain small. Since f_s is

proportional to $1/\tau$, the rate at which energy is pumped into (or extracted from) the laser inversion is limited by rotational relaxation.

From Eq. (6), τ_J increases with increasing J. Therefore, f_s is a decreasing function of the rotational quantum number. Rotational bottlenecking becomes stronger as J increases. At the same time, because of the increased rotational energy spacings, collisional quenching is believed to be less rapid with increasing J. An energy trapping-like characteristic results, which may be a contributing factor in the comparatively long but low-powered laser emissions observed for high J transitions.

The preceding formulation was extended to a multilevel system, and its predictions compared with those of the comprehensive rotational non-equilibrium model of Ref. 6. The major distinction between the two models is in the calculation of gain. The model described in Ref. 6 keeps track of the population of each v, J state and uses these in Eq. (1) to determine the gain for each transition. The present model keeps track of only the vibrational state populations. The Boltzmann distribution then is applied to obtain the equilibrated gains α^e , which are subsequently utilized in the multiband counterpart of Eq. (11) to obtain the nonequilibrium transition gains. The kinetics utilized in both models are identical. For consistency, the relaxation time-constant version of the Ref. 6 model is used.

A comparison of the predicted pulse outputs of the two models for an atmospheric pressure H₂-F₂ laser is given in Fig. 1. The pulses are nearly identical, even to the details of the individual "bumps" in the pulse shapes.

^{*}J. S. Whittier and R. Hofland, private communication, The Aerospace Corporation, El Segundo, California.




Fig. 1. Comparison of Pulse Outputs Predicted by Present Model and ROLAX

In Fig. 2, the model predictions of time resolved spectra for the same laser case are compared. The horizontal bars denote the intervals during which lasing is observed for the transitions designated on the vertical scale, where J is the rotational quantum number of the lower level of the transition.

Again, the predictions are nearly identical. This consistency is also observed in the relative energy distributions of the individual vibrational-rotational transitions of the six lasing bands. The amount of information attainable by the use of either model is the same. As demonstrated in the figures, the predictions are very close. The model of Ref. 6 explicitly computes the populations of the individual rotational states. In the present model, this information can be inferred from the calculated transition gains and vibrational populations.

The cost savings achieved by the present model are considerable. For the case described here, the execution time for the Ref. 6 model was 1640 sec on the CDC 7600 computer. For the present model, the time required is just 132 sec. The execution time of the corresponding model without rotational relaxation features ⁷ is 104 sec. Additional reductions in the present model run time are anticipated as the study progresses.

Since the rotational nonequilibrium model utilizing the technique described herein costs only slightly more to run than the corresponding equilibrium model, laser calculations with rotational relaxation taken into account can now be carried out routinely. Furthermore, parametric studies can be performed that will improve understanding of the importance of rotational relaxation in laser predictions. The technique is applicable to




Fig. 2. Comparison of Time-Resolved Spectra of Present Model and ROLAX

both pulsed and cw laser calculations. Of particular interest is its possible application to wave optics modeling of cw laser beam quality, where the added spectral realism afforded by considering rotational nonequilibrium can now be obtained at a much more reasonable cost.

REFERENCES

- J. B. Moreno, "Computer Model for the H₂ + F₂ Super-Radiant Laser,"
 AIAA Paper No. 75-36, 13th Aerospace Sciences Meeting, Pasadena,
 California, 20-22 January 1975.
- R. J. Hall, "Rotational Nonequilibrium and Line-Selected Operation in CW DF Chemical Lasers," J. Quantum Electron. QE-12, 453 (1976).
- 3. A. Ben-Shaul, K. L. Kompa, and U. Schmailzl, "Vib-Rotational Energy Distributions and Relaxation Processes in Pulsed HF Chemical Lasers," J. Chem. Phys. 65, 1711 (1976).
- L. H. Sentman, "Rotational Nonequilibrium in CW Chemical Lasers,"
 J. Chem. Phys. 62, 3523 (1975).
- J. G. Skifstad and C. M. Chao, "Rotational Relaxation in a Line-Selected Continuous HF Chemical Laser," Appl. Opt. 14, 1713 (1975).
- R. L. Kerber, K. A. Emery, and J. J. T. Hough, "Evaluation of Rotational Nonequilibrium Mechanisms in Pulsed H₂ + F₂ Lasers," <u>5th Conf. on Chemical and Molecular Lasers</u>, Paper No. MAI9, St. Louis, April 1977.
- J. J. T. Hough and R. L. Kerber, "Effect of Cavity Transients and Rotational Relaxation on the Performance of Pulsed HF Chemical Lasers: A Theoretical Investigation," Appl. Opt. 14, 2960 (1975).
- N. Cohen, <u>A Review of Rate Coefficients for Reactions in the H₂-F₂</u>
 <u>Laser System</u>, TR-0073(3430)-9, Aerospace Corporation, El Segundo,
 California (1 November 1972).



THE IVAN A. GETTING LABORATORIES

The Laboratory Operations of The Aerospace Corporation is conducting experimental and theoretical investigations necessary for the evaluation and application of scientific advances to new military concepts and systems. Versatility and flexibility have been developed to a high degree by the laboratory personnel in dealing with the many problems encountered in the nation's rapidly developing space and missile systems. Expertise in the latest scientific developments is vital to the accomplishment of tasks related to these problems. The laboratories that contribute to this research are:

Aerophysics Laboratory: Launch and reentry aerodynamics, heat transfer, reentry physics, chemical kinetics, structural mechanics, flight dynamics, atmospheric pollution, and high-power gas lasers.

Chemistry and Physics Laboratory: Atmospheric reactions and atmospheric optics, chemical reactions in polluted atmospheres, chemical reactions of excited species in rocket plumes, chemical thermodynamics, plasma and laser-induced reactions, laser chemistry, propulsion chemistry, space vacuum and radiation effects on materials, lubrication and surface phenomena, photosensitive materials and sensors, high precision laser ranging, and the application of physics and chemistry to problems of law enforcement and biomedicine.

Electronics Research Laboratory: Electromagnetic theory, devices, and propagation phenomena, including plasma electromagnetics; quantum electronics, lasers, and electro-optics; communication sciences, applied electronics, semi-conducting, superconducting, and crystal device physics, optical and acoustical imaging; atmospheric pollution; millimeter wave and far-infrared technology.

Materials Sciences Laboratory: Development of new materials; metal matrix composites and new forms of carbon; test and evaluation of graphite and ceramics in reentry; spacecraft materials and electronic components in nuclear weapons environment; application of fracture mechanics to stress corrosion and fatigue-induced fractures in structural metals.

Space Sciences Laboratory: Atmospheric and ionospheric physics, radiation from the atmosphere, density and composition of the atmosphere, aurorae and airglow; magnetospheric physics, cosmic rays, generation and propagation of plasma waves in the magnetosphere; solar physics, studies of solar magnetic fields; space astronomy, x-ray astronomy; the effects of nuclear explosions, magnetic storms, and solar activity on the earth's atmosphere, ionosphere, and magnetosphere; the effects of optical, electromagnetic, and particulate radiations in space on space systems.

THE AEROSPACE CORPORATION El Segundo, California